

BOARD AND BATTEN  
KAYCAN

# Board and Batten

SKU: KAYCAN-BOARD-AND-BATTEN

**GAUGE**

3/8 in. (0.95 cm)

**WARRANTY**

25-year limited warranty against buckling, peeling, separating, and chipping

**COLOURS**

4 available

**PROFILES**

Board and Batten

Board and Batten by Maibec CanExel brings the timeless modern farmhouse aesthetic to engineered wood siding. Vertical panels feature a textured HDF substrate with factory-applied finish and an easy-to-install hidden-fastener interlock system. Available in 4 colours — Black, Granite, Mist Grey, and White — with actual coverage of 11 sq. ft. per 12-foot board and a prorated 25-year limited warranty.


## Key Features

- Farmhouse style with Maibec CanExel unique woodgrain finish
- Can only be installed vertically
- Prorated 25-year limited warranty
- Easy-to-install Maibec CanExel Interlock system
- Actual coverage of 11 square feet per 12-foot board

## Available Colours

### STANDARD

4 colours




## Profiles & Specifications

### BOARD

Board

The wide vertical board panel. Hidden fastener interlock system. Textured HDF substrate with factory-applied finish.



Length	12 ft. (3.66 m)
Panels / Box	4 boards/bundle · 44 sq. ft. per bundle
Coverage	30 bundles per pallet
Nominal Width	12 in. (30.48 cm)
Actual Width	11 7/8 in. (30.16 cm)
Nominal Thickness	3/8 in. (0.95 cm)
Substrate	HDF (High-density fiberboard, 960 kg/m <sup>3</sup> )
Finish	Textured
Installation	Hidden fasteners

### BATTEN

Batten

The narrow batten strip installed over the board joints. Pre-drilled every 16" for nailing through both batten and board.

Length	12 ft. (3.66 m)
Panels / Box	8 battens/bundle · 45 bundles per pallet
Nominal Width	2 1/4 in. (5.72 cm)
Nominal Thickness	3/8 in. (0.95 cm)
Substrate	HDF
Installation	Regular — nailed at 16" O.C.

## Compatible Accessories

Starter Strip	J-Trim 1/2"	J-Trim 1"
Drip Cap	Outside Corner 1/2"	Outside Corner 1"
H Trim 1/2"	Joint Cover 9"	Joint Cover 12"
Anti-Rodent Trim	Caulking	Nails
Rolls	Touch-Up Paint	

## Installation Guide

### Critical Installation Rules

- 1 Can only be installed vertically — no horizontal installation permitted
- 2 Double furring is mandatory in Quebec and the Maritimes; strongly recommended in Ontario
- 3 Install vertical furring strips (min. 3/8" thick), then horizontal 1"x3" furring strips every 16" over top
- 4 Maintain minimum 1-1/4" fastener penetration into stud, strapping, or combination thereof
- 5 Spiral shank nails require minimum 1-1/8" stud penetration
- 6 Batten nails must be a minimum of 2" long — pre-drill every 16" through batten and board
- 7 Center the batten above the groove and nail at 16" O.C.
- 8 Touch-up all visible nails immediately after installation to prevent moisture ingress
- 9 For horizontal batten trim, install Z-flashing on top of the trim; add a second Z-flashing at the lower end
- 10 Never recut the batten — the original factory paint must remain on the edge
- 11 Keep siding in a dry, unheated, well-ventilated area, at least 6" off the ground during storage
- 12 Maintain minimum 8" (203 mm) clearance between the bottom edge of siding and grade
- 13 Seal all gaps between siding and trim with a high-quality, non-hardening sealant; leave 3/16" expansion gap at trim junctions

**Storage & Handling**

- Inspect siding visually once a year
- Clean with a low-pressure garden hose (under 100 psi) — NEVER use a pressure washer
- For stubborn dirt, use a soft bristle brush with non-abrasive laundry detergent (1/3 cup per 3 litres of water); rinse thoroughly
- NEVER use harsh/abrasive detergents, pressure washers, or products containing acids, ammonia, or bleach
- Touch-up all bare wood areas with touch-up paint matching the factory colour
- Check and redo sealant joints as soon as they begin to harden or crack



# KAYCAN

## Ready to order?

Submit your spec list and we'll respond with pricing and availability - usually within one business day.

### WEB

[promaterials.ca](http://promaterials.ca)

### PHONE

(905) 836-7272

### EMAIL

[info@promaterials.ca](mailto:info@promaterials.ca)

### ADDRESS

Unit 5, 1235 Journey's End Cir, Newmarket, ON