

7" BEADED SOFFIT
MITTEN

Mitten 7" Beaded Soffit

SKU: MITT-SF-B7

GAUGE

.040"

WARRANTY

Lifetime Transferable Warranty

COLOURS

1 available

PROFILES

2 Profiles: Solid | Hidden Vent

Mitten 7" Beaded Soffit combines a classic beaded panel profile with the performance and durability of premium vinyl. The 7" wide panel covers eaves with a clean, traditional look. Choose Solid for a fully closed eave, or Hidden Vent for 2.66 sq.in./ft of concealed ventilation that promotes airflow and prevents moisture buildup in your roof structure.

Key Features

- 7" wide beaded panel — single profile for a traditional, finished look
- .040" premium gauge vinyl — will not rot, peel, chip, flake, or blister
- Promotes directional airflow through roof structure to eliminate moisture-related decay
- CCMC Acceptance No. 06419L
- Available in Frost
- Hidden Vent system: 2.66 sq.in./ft Net Free Air Intake, fully concealed for a clean appearance
- 28 panels per carton — 200 sq. ft. coverage
- Lifetime non-prorated transferable warranty
- ASTM E84 Flame Spread Index: 20

Available Colours

STANDARD

1 colour



Frost

Profiles & Specifications

B7-S

7" Beaded Solid



Length	12' (3.66 m)
Height / Width	7" (17.8 cm)
Thickness	.040"
Panels / Box	28 pcs/ctn
Coverage	200 sq. ft. (18.58 m ²)
Installation	Horizontal — Soffit

B7-HV

7" Beaded Hidden Vent



Length	12' (3.66 m)
Height / Width	7" (17.8 cm)
Thickness	.040"
Panels / Box	28 pcs/ctn
Coverage	200 sq. ft. (18.58 m ²)
Installation	Horizontal — Soffit

* Net Free Air Intake: 2.66 sq.in./ft — Hidden Vent system for a clean, stylish look with superior ventilation

Certifications & Testing Standards

Mitten 7" Beaded Soffit meets or exceeds the following Canadian and international performance standards.

- CAN/CGSB-41.24.95
- CCMC Acceptance No. 06419L
- ASTM D3679
- ASTM D4216 — cell classification 13344B
- ASTM D1929 — Self-Ignition Temperature 824°F (440°C)
- ASTM E84 — Flame Spread 20 | Fuel Contribution 0 | Smoke Development 360
- ASTM E119 — 1-Hour Fire Endurance (wall assembly)
- ASTM D4226 — Wind & Impact Resistance
- VSI Certified Installer Program

Compatible Accessories

½" J-Channel

—

½" F-Channel

—

Fascia

—

Fascia J

—



MITTEN

Ready to order?

Submit your spec list and we'll respond with pricing and availability - usually within one business day.

WEB

promaterials.ca

PHONE

(905) 836-7272

EMAIL

info@promaterials.ca

ADDRESS

Unit 5, 1235 Journey's End Cir, Newmarket, ON