

M-SERIES ALUMINUM
MITTEN

M-Series Aluminum

SKU: MITTEN-ALUM-M

GAUGE

.013" soffit · .024" gutter coil ·
heavy gauge trim coil

WARRANTY

Lifetime Transferable Warranty

COLOURS

13 available

PROFILES

Quad 4 Soffit / Fascia / Trim
Coil / Gutter Coil / Downspout /
Elbow

Mitten M-Series Aluminum makes it easy to dress up any home or light commercial building with a coordinated system of soffit, fascia, and drainage products. The Quad 4 Aluminum Soffit — available in solid and vented versions — delivers a clean 16" panel profile with 5.16 sq.in. of net free air intake per linear foot on the vented option. Smooth and ribbed fascia in four widths, heavy-gauge trim coil, gutter coil, downspouts, and elbows complete the system. All products are available in 13 colours specifically selected to match or complement the full Mitten vinyl siding palette.

Key Features

- Complete soffit, fascia & drainage system in one collection
- Fascia in smooth & ribbed profiles — 6", 8", 8.5" and 10" widths
- Gutter Coil .024" — 1SP and 2SP for seamless gutters
- 13 colours matched to Mitten vinyl siding palette
- Quad 4 Soffit — solid and vented (5.16 sq.in./LF ventilation)
- Heavy-gauge Trim Coil — 1SP and 2SP options
- Downspouts & elbows — 3 cross-section sizes
- Lifetime Transferable Warranty

Available Colours

M-SERIES

13 colours




Profiles & Specifications

Q4S

Quad 4 Soffit

Aluminum soffit panel with four 4" ribs across a 16" width. Available in Solid and Vented versions. The vented version provides 5.16 sq.in. net free air intake per linear foot for proper attic ventilation.



Length	12' (3.66 m)
Height / Width	16" (40.64 cm)
Thickness	.013"
Panels / Box	2 squares/box
Coverage	288 sq.ft./box (26.76 m ²)
Installation	Horizontal soffit application

* Colours: Terratone, Bone, Black, Brownstone, Dark Bronze, Flagstone, Hearthstone, Iron Ore, Musket Brown, Rockaway Grey, Slate, Stratus, White. Flagstone available in Eastern Canada only.

FAS

Fascia

Aluminum fascia available in smooth and ribbed profiles. Multiple widths to suit different framing conditions. 8" width available in Eastern Canada only; 8.5" width available in Western Canada only.



Length	Standard lengths
Height / Width	6" 8"† 8.5"* 10"
Installation	Horizontal fascia application at roof eave

* † 8" Eastern Canada only · * 8.5" Western Canada only

TC

Trim Coil

Heavy-gauge aluminum coil for field-forming trim, wrapping, and finishing work. Available one side painted (1SP) or two sides painted (2SP).



Length	30 m roll
Height / Width	24"

* Used for custom trim fabrication, fascia wrapping, and finish details.

GC

Gutter Coil

Aluminum coil for fabricating seamless gutters on site. Available one side painted (1SP) or two sides painted (2SP).



Length	Roll stock
Height / Width	11.875"
Thickness	.024"

DS

Downspout

Aluminum downspout for rainwater drainage. Multiple cross-section sizes available. 2"x3" and 3"x3" sizes available in Eastern Canada only.



* † Eastern Canada only

EL

Elbow

Aluminum elbow fitting for downspout direction changes. Matches downspout cross-section sizes. 2"x3" and 3"x3" sizes available in Eastern Canada only.



* † Eastern Canada only

Compatible Accessories

½" Universal J Trim

Universal fit — for soffit perimeter and edge finishing

5" End Cap Left

Closes open end of 5" soffit channel at left termination

5" End Cap Right

Closes open end of 5" soffit channel at right termination

5" Inside Box Miter

Inside corner box miter for 5" soffit

5" Inside Strip Miter

Inside corner strip miter for 5" soffit

5" Outside Box Miter

Outside corner box miter for 5" soffit

5" Outside Strip Miter

Outside corner strip miter for 5" soffit

10' Roof Edge

10' aluminum roof edge drip profile

Installation Guide

- 1 Ensure all framing, fascia boards, and soffit nailing surfaces are level and secure before installation.

- 2 Install J-channel along the wall and fascia perimeter first to receive soffit panel edges.

- 3 Slide soffit panels into J-channel from one side; fasten through slots with aluminum nails or screws — do not over-drive fasteners; leave room for thermal expansion.

- 4 For vented soffit: position the vented panels evenly across the soffit run for balanced airflow. Maintain a minimum 1:150 net free ventilation ratio per local building code.

- 5 Fascia: remove old wood fascia or apply directly over existing material if sound. Overlap joints by minimum 1" and stagger from soffit joints.

- 6 Trim Coil: use a brake to form site-cut trim pieces. Cut with snips; never use a saw (leaves sharp burrs). Overlap trim coil joints minimum ½".

- 7 Gutter Coil: fabricate seamless gutters on site using a gutter machine. Slope gutters minimum 1/4" per foot toward downspout outlets.

- 8 Downspouts and elbows: secure downspouts to wall with straps every 6 ft maximum. Keep bottom of downspout minimum 6" above grade.

- 9 Avoid contact between aluminum and dissimilar metals (copper, iron) to prevent galvanic corrosion — use aluminum or stainless fasteners throughout.

- 10 Flagstone colour is available in Eastern Canada only. 8" fascia is Eastern Canada only; 8.5" fascia is Western Canada only.



MITTEN

Ready to order?

Submit your spec list and we'll respond with pricing and availability - usually within one business day.

WEB

promaterials.ca

PHONE

(905) 836-7272

EMAIL

info@promaterials.ca

ADDRESS

Unit 5, 1235 Journey's End Cir, Newmarket, ON