

DOUBLE 5" SOFFIT
MITTEN

Mitten Double 5" Soffit

SKU: MITT-SF-D5

GAUGE

.040"

WARRANTY

Lifetime Transferable Warranty

COLOURS

9 available

PROFILES

2 Profiles: Solid | Perforated Full Vent

Mitten Double 5" Soffit delivers bold, clean eave coverage with a distinctive U-groove profile. Choose Solid for a seamless look — or as a vertical siding accent — or Perforated Full Vent for 4.2 sq.in./ft Net Free Air Intake. Available in 9 colours including four Variegated shades exclusive to the Double 5".

Key Features

- U-groove design — double 5" panel, 10" wide
- Solid panel doubles as vertical siding accent
- 200 sq. ft. per carton (20 panels)
- Lifetime non-prorated transferable warranty
- ASTM E84 Flame Spread Index: 20
- Perforated Full Vent: 4.2 sq.in./ft Net Free Air Intake
- .040" premium gauge vinyl
- 4 exclusive Variegated colours: Arctic Grey, Burnt Sienna, Farmhouse, Hemlock
- CCMC Acceptance No. 06419L
- 9 colours total

Available Colours

VARIEGATED


4 colours



Arctic Grey Burnt Sienna Farmhouse Hemlock

STANDARD

5 colours



Frost Bone Brownstone Hearthstone Stratus

Profiles & Specifications

D5-S

Double 5" Solid



Length	12' (3.66 m)
Height / Width	10" (25.4 cm)
Thickness	.040"
Panels / Box	20 pcs/ctn
Coverage	200 sq. ft. (18.58 m ²)
Installation	Horizontal — Soffit / Vertical Siding Accent

D5-P

Double 5" Perforated



Length	12' (3.66 m)
Height / Width	10" (25.4 cm)
Thickness	.040"
Panels / Box	20 pcs/ctn
Coverage	200 sq. ft. (18.58 m ²)
Installation	Horizontal — Soffit

* Net Free Air Intake: 4.2 sq.in./ft (Full Vent)

Certifications & Testing Standards

Mitten Double 5" Soffit meets or exceeds the following Canadian and international performance standards.

● CAN/CGSB-41.24.95
● CCMC Acceptance No. 06419L
● ASTM D3679
● ASTM D4216 — cell classification 13344B
● ASTM D1929 — Self-Ignition Temperature 824°F (440°C)
● ASTM E84 — Flame Spread 20 Fuel Contribution 0 Smoke Development 360
● ASTM E119 — 1-Hour Fire Endurance (wall assembly)
● ASTM D4226 — Impact Strength
● ASTM D2244 — Colour Tolerance "d3 Hunter units (premium) / "d4 Hunter units (standard)
● VSI Certified Installer Program

Compatible Accessories

½" J-Channel —	½" F-Channel —	Fascia —
Fascia J —		



MITTEN

Ready to order?

Submit your spec list and we'll respond with pricing and availability - usually within one business day.

WEB

promaterials.ca

PHONE

(905) 836-7272

EMAIL

info@promaterials.ca

ADDRESS

Unit 5, 1235 Journey's End Cir, Newmarket, ON