

JAMB-FIT™ SOFFIT  
MITTEN

# Mitten Jamb-Fit™ Soffit

SKU: MITT-SF-JF

**GAUGE**

.040"

**WARRANTY**

Lifetime Transferable Warranty

**COLOURS**

5 available

**PROFILES**

4 Profiles: JF8" Solid | JF8" Perforated | JF16" Solid | JF16" Perforated

Mitten Jamb-Fit™ Soffit offers a practical slide-lock installation system in two widths: the 8" (Double 4") covers a full palette of 5 colours, while the 16" (Quad 4") is ideal for wider eave spans and delivers 6.26 sq.in./ft of Net Free Air Intake in its perforated variant. Both sizes share the same 192 sq. ft. per carton and lifetime non-prorated transferable warranty.


## Key Features

- Easy slide-lock installation system for fast, secure fitting
- JF8" Perforated: 3.14 sq.in./ft Net Free Air Intake
- .040" premium gauge vinyl
- JF8" available in 5 colours including Black
- Lifetime non-prorated transferable warranty
- ASTM E84 Flame Spread Index: 20
- Two sizes: JF8" (Double 4" / 8" wide) and JF16" (Quad 4" / 16" wide)
- JF16" Perforated: 6.26 sq.in./ft Net Free Air Intake — ideal for wider eave spans
- 192 sq. ft. coverage per carton across both sizes
- JF16" available in Frost
- CCMC Acceptance No. 06419L

## Available Colours

### STANDARD

4 colours



Frost

Bone

Stratus

Brownstone

### BOLD

1 colour



Black

## Profiles & Specifications

### JF8-S

Jamb-Fit™ 8" Solid

Double 4" profile — 8" wide solid panel



Length	12' (3.66 m)
Height / Width	8" (20.32 cm)
Thickness	.040"
Panels / Box	24 pcs/ctn
Coverage	192 sq. ft. (17.84 m <sup>2</sup> )
Installation	Horizontal — Soffit

### JF8-P

Jamb-Fit™ 8" Perforated

Double 4" profile — 8" wide perforated panel



Length	12' (3.66 m)
Height / Width	8" (20.32 cm)
Thickness	.040"
Panels / Box	24 pcs/ctn
Coverage	192 sq. ft. (17.84 m <sup>2</sup> )
Installation	Horizontal — Soffit

\* Net Free Air Intake: 3.14 sq.in./ft

### JF16-S

Jamb-Fit™ 16" Solid

Quad 4" profile — 16" wide solid panel for wider eave spans



Length	12' (3.66 m)
Height / Width	16" (40.64 cm)
Thickness	.040"
Panels / Box	12 pcs/ctn
Coverage	192 sq. ft. (17.84 m <sup>2</sup> )
Installation	Horizontal — Soffit

**JF16-P**

Jamb-Fit™ 16" Perforated

Quad 4" profile — 16" wide perforated panel for wider eave spans



Length	12' (3.66 m)
Height / Width	16" (40.64 cm)
Thickness	.040"
Panels / Box	12 pcs/ctn
Coverage	192 sq. ft. (17.84 m <sup>2</sup> )
Installation	Horizontal — Soffit

\* Net Free Air Intake: 6.26 sq.in./ft

## Certifications & Testing Standards

Mitten Jamb-Fit™ Soffit meets or exceeds the following Canadian and international performance standards.

• CAN/CGSB-41.24.95
• CCMC Acceptance No. 06419L
• ASTM D3679
• ASTM D4216 — cell classification 13344B
• ASTM D1929 — Self-Ignition Temperature 824°F (440°C)
• ASTM E84 — Flame Spread 20   Fuel Contribution 0   Smoke Development 360
• ASTM E119 — 1-Hour Fire Endurance (wall assembly)
• ASTM D4226 — Wind & Impact Resistance
• VSI Certified Installer Program

## Compatible Accessories

<p><b>½" J-Channel</b></p> <p>—</p>	<p><b>½" F-Channel</b></p> <p>—</p>	<p><b>Fascia</b></p> <p>—</p>
<p><b>Fascia J</b></p> <p>—</p>		



# MITTEN

## Ready to order?

Submit your spec list and we'll respond with pricing and availability - usually within one business day.

**WEB**

[promaterials.ca](http://promaterials.ca)

**PHONE**

(905) 836-7272

**EMAIL**

[info@promaterials.ca](mailto:info@promaterials.ca)

**ADDRESS**

Unit 5, 1235 Journey's End Cir, Newmarket, ON