

TRIPLE 4" SOFFIT
MITTEN

Mitten Triple 4" Soffit

SKU: MITT-SF-T4

GAUGE

.040"

WARRANTY

Lifetime Transferable Warranty

COLOURS

7 available

PROFILES

5 Profiles: Solid | Perf. Full Vent
| Perf. Center Vent | Lanced Full
Vent | Lanced Center Vent

Mitten Triple 4" Soffit provides essential ventilation and a clean, finished appearance for any eave or roofline. With five profiles offering airflow from 1.96 to 7.2 sq.in./ft of net free air intake, it meets any building code ventilation requirement. Available in 7 colours with a lifetime non-prorated transferable warranty.


Key Features

- 5 ventilation profiles in one system
- Deep ½" panel projection for sharp definition
- 192 sq. ft. per carton
- CCMC Acceptance No. 06419L
- 7 colours including Black and Musket Brown
- Net Free Air Intake up to 7.2 sq.in./ft (Lanced Full Vent)
- .040" premium gauge
- Lifetime non-prorated transferable warranty
- ASTM E84 Flame Spread Index: 20
- Musket Brown available in Perforated Full Vent only

Available Colours

STANDARD

6 colours



BOLD

1 colour



Profiles & Specifications

T4-S

T4" Solid



Length	12' (3.66 m)
Height / Width	12" (30.48 cm)
Thickness	.040"
Panels / Box	16 pcs/ctn
Coverage	192 sq. ft. (17.84 m ²)
Installation	Horizontal — Soffit

T4-PFV

T4" Perforated Full Vent



Length	12' (3.66 m)
Height / Width	12" (30.48 cm)
Thickness	.040"
Panels / Box	16 pcs/ctn
Coverage	192 sq. ft. (17.84 m ²)
Installation	Horizontal — Soffit

* Net Free Air Intake: 5.89 sq.in./ft | All 7 colours available including Musket Brown

T4-PCV

T4" Perforated Center Vent



Length	12' (3.66 m)
Height / Width	12" (30.48 cm)
Thickness	.040"
Panels / Box	16 pcs/ctn
Coverage	192 sq. ft. (17.84 m ²)
Installation	Horizontal — Soffit

* Net Free Air Intake: 1.96 sq.in./ft

T4-LFV

T4" Lanced Full Vent



Length	12' (3.66 m)
Height / Width	12" (30.48 cm)
Thickness	.040"
Panels / Box	16 pcs/ctn
Coverage	192 sq. ft. (17.84 m ²)
Installation	Horizontal — Soffit

* Net Free Air Intake: 7.2 sq.in./ft

T4-LCV

T4" Lanced Center Vent



Length	12' (3.66 m)
Height / Width	12" (30.48 cm)
Thickness	.040"
Panels / Box	16 pcs/ctn
Coverage	192 sq. ft. (17.84 m ²)
Installation	Horizontal — Soffit

* Net Free Air Intake: 2.4 sq.in./ft

Certifications & Testing Standards

Mitten Triple 4" Soffit meets or exceeds the following Canadian and international performance standards.

- CAN/CGSB-41.24.95
- CCMC Acceptance No. 06419L
- ASTM D3679
- ASTM D4216 — cell classification 13344B
- ASTM D1929 — Self-Ignition Temperature 824°F (440°C)
- ASTM E84 — Flame Spread 20 | Fuel Contribution 0 | Smoke 360
- ASTM E119 — 1-Hour Fire Endurance (wall assembly)
- ASTM D4226 — Wind & Impact Resistance
- VSI Certified Installer Program

Compatible Accessories

½" J-Channel

—

½" F-Channel

—

Fascia

—

Fascia J

—



MITTEN

Ready to order?

Submit your spec list and we'll respond with pricing and availability - usually within one business day.

WEB

promaterials.ca

PHONE

(905) 836-7272

EMAIL

info@promaterials.ca

ADDRESS

Unit 5, 1235 Journey's End Cir, Newmarket, ON