

NOVIKSHAKE HAND-SPLIT SHAKE
NOVIK

NovikShake HS Hand-Split Shake

SKU: NOVIK-HS

WEIGHT

3.1 lbs / 1.4 kg per panel

WARRANTY

Lifetime Limited Warranty

COLOURS

14 available

PROFILES

HS — Hand-Split Shake

NovikShake HS delivers the rugged, authentic look of hand-split cedar shakes with the durability and low maintenance of polypropylene. Inspired by the Viking method of splitting wood, it's available in 14 colours across Blended and Solid finish groups — from rich multi-tonal Weathered Blend to clean, bold Anthracite. Moisture-impervious from ground level to the roofline, installs with traditional tools, and backed by a Lifetime Limited Warranty. Certified under CCMC 13420-R, ICC-ES ESR-2888, and TDI.

Key Features

- Professional grade — light enough for one-person installation in a fraction of the time
- Seamless joints — attractive visual appearance
- Durable — resistant to rotting, warping, cracking, expansion, and contraction
- Lifetime Limited Warranty
- 14 colours in Blended and Solid finish groups
- Easy to install using traditional tools
- Impervious to moisture — can be installed at ground level or at the roofline without rot, split, or decay
- Requires little to no maintenance — no painting, staining, or caulking required
- CCMC 13420-R / ICC-ES ESR-2888 / TDI approved

Available Colours

BLENDED

6 colours



Weathered Blend Cedar Blend Canyon Blend Basalt Brownstone Anthracite

SOLID

8 colours



Windsor Blue Brunswick Green Coventry Gray Rockaway Gray Coffee Bean Sandstone Heritage Gray White

Profiles & Specifications

HS-BL

Hand-Split Shake — Blended

The Hand-Split Shake Blended profile combines multiple accent colours for rich tones, hues, and shades that offer subtle depth and complexity — replicating the dimensional look of real hand-split cedar shakes. Inspired by the Viking method of splitting wood, this profile delivers a rugged, rustic character with the ease and durability of polypropylene.




Length	45.1" exp. / 48.38" full (114.6 cm / 122.87 cm)
Height / Width	17.5" exp. / 18.75" full (44.5 cm / 47.63 cm)
Panel Weight	3.1 lbs (1.4 kg) per panel
Panels / Box	9 pcs/box
Coverage	Approx. 1/2 sq. (4.6 m ²) per box
Installation	Horizontal — full facade or accent zones

* Corner dimensions: 4.8" x 9.3" exp. / 4.8" x 19.3" full (12.1 cm x 23.5 cm exp. — 12.1 cm x 48.9 cm full) | 5 corners per box. Available in all Blended colours.

HS-SO

Hand-Split Shake — Solid

The Hand-Split Shake Solid profile delivers the look of painted cedar shingles in a wide range of popular colours. Single solid colour throughout for a clean, consistent appearance — ideal for bold, modern designs or coordinating with vinyl siding.



Length	45.1" exp. / 48.38" full (114.6 cm / 122.87 cm)
Height / Width	17.5" exp. / 18.75" full (44.5 cm / 47.63 cm)
Panel Weight	3.1 lbs (1.4 kg) per panel
Panels / Box	9 pcs/box
Coverage	Approx. 1/2 sq. (4.6 m ²) per box
Installation	Horizontal — full facade or accent zones

* Corner dimensions: 4.8" x 9.3" exp. / 4.8" x 19.3" full (12.1 cm x 23.5 cm exp. — 12.1 cm x 48.9 cm full) | 5 corners per box. Available in all 8 Solid colours.

Certifications & Testing Standards

NovikShake HS Hand-Split Shake meets or exceeds the following Canadian and international performance standards.

- CCMC 13420-R — National Research Council of Canada, certified July 7, 2009, revised February 5, 2021
- ICC-ES ESR-2888 — International Code Council Evaluation Service, revised February 2021
- TDI Approvals EC-110 — Texas Department of Insurance wind resistance, effective October 1, 2019
- MasterFormat 07 46 33.04 — Polypropylene Siding classification
- ASTM D7254 — Standard Specification for Polypropylene (PP) Siding
- Lifetime Limited Warranty

Compatible Accessories

Universal Starter Strip

For all HS profiles

Sets the first row of Hand-Split Shake panels at the correct angle. Ensures a level, uniform installation from the base row up. Nail through holes at maximum 8" (20.32 cm) intervals.

NovikTrim J-Channel

For openings and edges

Used around windows, doors, and all perimeter edges. Leave a 1/4" (0.64 cm) gap between trim and siding panel end. Installation video available from Novik — ask us for the link.

Blended Outside Corner

4.8" x 9.3" exp. / 4.8" x 19.3" full — 5 pcs/box

Outside corner trim matched to Hand-Split Shake Blended colours (Weathered Blend, Cedar Blend, Canyon Blend, Basalt, Brownstone, Anthracite). Exposed: 4.8" x 9.3" | Full: 4.8" x 19.3" | 5 corners per box.

Solid Outside Corner

4.8" x 9.3" exp. / 4.8" x 19.3" full — 5 pcs/box

Outside corner trim available in all 8 Hand-Split Shake Solid colours. Exposed: 4.8" x 9.3" | Full: 4.8" x 19.3" | 5 corners per box.

Installation Guide

- 1 Always begin installation at the lowest point of the structure and work upward, left to right. Install a Universal Starter Strip on the first row, ensuring the horizontal starting line is perfectly level and square with the wall. Leave a 2½" (6.35 cm) gap at each end of the wall when using decorative corners.
- 2 Use non-corrosive (aluminum or galvanized) roofing nails or screws: minimum 1¼" (3.18 cm) penetration into solid substrate. Head diameter: minimum 0.4" (1 cm). Nail at maximum 16" (40.64 cm) o.c. intervals through the center of each nailing slot. Each full-length panel requires a minimum of 6 nails — nail the center hole first, then both end holes, the lateral hole, and 2 additional nails in the nailing channel. Never hammer nails flush — leave a 1/16" (0.16 cm) gap to allow for thermal movement.
- 3 Temperature adjustment is required: above 40°F (5°C) — slide panel to the right stopper; below 40°F (5°C) — adjust panel to the temperature line indicated. Never force panels tight — polypropylene expands and contracts seasonally. Polymer undergoes expansion/contraction due to temperature variations; always follow installation instructions to allow for movement.
- 4 Outside corners: install decorative corner trim first. Siding panels must finish at 2½" (6.35 cm) from the corner of the wall; nail siding at 4" (10.2 cm) from the wall edge. Stagger panel joints row to row — begin each new row with a 12" (30.5 cm) offset from the row below; never align vertical panel joints between adjacent rows.
- 5 On masonry or furring walls: install furring strips at maximum 8" (20.32 cm) o.c. vertically (minimum 19 mm x 38 mm). One furring strip must align behind every nail hole. Fasteners must penetrate a minimum of 38 mm into solid framing or sheathing. Continuous, clear air space of 19 mm outboard of the sheathing membrane is required under CCMC 13420-R.
- 6 Inside corners can be finished with: (A) an inside corner post, (B) two J-trims, or (C) two NovikTrim1 pieces. Seal the inside corner of the wall before installing any trim. Leave a ¼" (0.64 cm) gap between any trim and siding panel ends.
- 7 Care & cleaning: Hand-Split Shake requires no painting, staining, or caulking. Clean annually with plain water and a garden hose or a mild diluted detergent (1/3 cup laundry detergent per 4 quarts water) with a soft-bristle brush. Do not use a pressure washer, abrasive cleaners, or strong solvents — pressure washing will void the warranty. Clean bottom-up; rinse top-down with clear water.



NOVIK

Ready to order?

Submit your spec list and we'll respond with pricing and availability - usually within one business day.

WEB

promaterials.ca

PHONE

(905) 836-7272

EMAIL

info@promaterials.ca

ADDRESS

Unit 5, 1235 Journey's End Cir, Newmarket, ON