

NOVIKSHAKE NORTHERN PERFECTION  
NOVIK

# NovikShake Northern Perfection

SKU: NOVIK-NP

**WEIGHT**

2.5 lbs / 1.13 kg per panel

**WARRANTY**

Lifetime Limited Warranty

**COLOURS**

10 available

**PROFILES**

NP — Architecturally Accurate  
5" Shake

NovikShake Northern Perfection combines the authentic look of an architecturally accurate 5" shake with the durability and low maintenance of polypropylene. Available in 10 colours matched to Mitten's most popular vinyl siding lines, it installs easily with traditional tools and is moisture-impervious from ground level to the roofline. Backed by a Lifetime Limited Warranty and certified under CCMC 13420-R, ICC-ES, and TDI standards — Northern Perfection is built for Canadian climates.

## Key Features

- Professional grade — light enough for one-person installation in a fraction of the time
- Seamless joints with fine wood grain and saw cut texture — attractive visual appearance
- Durable — resistant to rotting, warping, cracking, expansion, and contraction
- Architecturally accurate 5" shake width — traditional look on any structure
- CCMC 13420-R / ICC-ES / TDI approved
- Easy to install using traditional tools
- Impervious to moisture — can be installed at ground level or at the roofline without rot, split, or decay
- Requires little to no maintenance — no painting, staining, or caulking required
- 10 colours matched to Mitten vinyl siding — full whole-home coordination
- Lifetime Limited Warranty

## Available Colours



## Profiles & Specifications



An architecturally accurate 5" shake that offers the perfect blend between traditional and modern. Seamless joints with a fine wood grain and saw cut texture provide a lasting, traditional look to any structure.



Length	42.6" exp. / 47" full (108.3 cm / 119.4 cm)
Height / Width	15" exp. / 16.6" full (38.1 cm / 42.2 cm)
Panel Weight	2.5 lbs (1.13 kg) per panel
Panels / Box	11 pcs/box
Coverage	Approx. 1/2 sq. (50 sq. ft.) per box
Installation	Horizontal — full facade or accent zones

\* Corner dimensions: 3.8" x 15" exp. / 3.8" x 16.8" full (9.5 cm / 38.1 cm exp. — 9.5 cm / 42.6 cm full) | 5 corners per box.

## Certifications & Testing Standards

NovikShake Northern Perfection meets or exceeds the following Canadian and international performance standards.

- CCMC 13420-R — National Research Council of Canada, certified February 8, 2021
- ICC-ES — International Code Council Evaluation Service approval
- TDI Approvals — Texas Department of Insurance wind resistance
- MasterFormat 07 46 33.04 — Polypropylene Siding classification
- Lifetime Limited Warranty

## Compatible Accessories

<p><b>Universal Starter Strip</b> For all NP profiles Sets the first row of Northern Perfection panels at the correct angle. Ensures level, uniform installation from the base row up.</p>	<p><b>NovikTrim J-Channel</b> For openings and edges Used around windows, doors, and all perimeter edges. Provides a clean, finished look and protects panel ends. Installation video available from Novik — ask us for the link.</p>	<p><b>NP Outside Corner</b> 3.8" x 15" exp. / 3.8" x 16.8" full — 5 pcs/box Outside corner trim precisely matched to Northern Perfection. Exposed: 3.8" x 15"   Full: 3.8" x 16.8"   5 corners per box. Available in all 10 NP colours.</p>
--	---	---

## Installation Guide

- 1 Start at the lowest point and work upward, left to right. Install a Universal Starter Strip on the first row to ensure correct panel angle and alignment.
- 2 Use non-corrosive (aluminum or galvanized) roofing nails: minimum 1-1/2" (3.81 cm) penetration into solid wood substrate. Nail at every stud — maximum 16" (40.64 cm) o.c. intervals.
- 3 Temperature adjustment is required: above 60°F (15°C) — position panel to the right stopper; between 20°–60°F — slide panel to the temperature line; below 20°F (-7°C) — add 1/8" (3 mm) right of the cold line. Never force panels tight — polypropylene expands and contracts seasonally.
- 4 Outside corners: install NP Outside Corner trim first, then butt siding panels snugly to the corner. Stagger panel joints row to row — never align vertical panel joints between adjacent rows.
- 5 On masonry or furring walls: install 1" x 3" (2.54 cm x 7.62 cm) wood furring strips at maximum 8" (20.32 cm) o.c. vertically. One furring strip must align behind every nail hole.
- 6 Care & cleaning: Northern Perfection requires no painting, staining, or caulking. Clean with mild soap and water using a soft cloth or low-pressure wash. Avoid abrasive cleaners or high-pressure washing directed at panel edges.



# NOVIK

## Ready to order?

Submit your spec list and we'll respond with pricing and availability - usually within one business day.

### WEB

[promaterials.ca](http://promaterials.ca)

### PHONE

(905) 836-7272

### EMAIL

[info@promaterials.ca](mailto:info@promaterials.ca)

### ADDRESS

Unit 5, 1235 Journey's End Cir, Newmarket, ON