

RESTORATION MILLWORK®  
CERTAINTEED

# Restoration Millwork® Interior PVC Trim

SKU: CT-RM-INTERIOR-PVC-TRIM

## WARRANTY

25-year limited warranty

## PROFILES

Cove · Regular Baseboard · Regular Casing · Classic Casing ·  
Colonial Baseboard · Century Baseboard · Century Casing

Restoration Millwork® Interior PVC Trim by CertainTeed brings the durability of cellular PVC indoors. Twelve SKUs across seven classic profile shapes — PVC Cove, Regular Baseboard, Regular Casing, Classic Casing, Colonial Baseboard, Century Baseboard, and Century Casing — install exactly like top-grade lumber using standard woodworking tools, but will never warp, split, or absorb moisture. FinishedEdge™ heat-sealed edges and TrueTexture™ woodgrain finish deliver a premium look right out of the box. A removable protective film guards against scuffs during transit and installation. Ships natural white and fully paintable to complement any colour scheme. Class A Flame Spread rated, ICC and CCMC compliant, and backed by a 25-year limited warranty.


## Key Features

- Natural white and ready to install
- Can be painted to complement any colour scheme
- TrueTexture™ — woodgrain finish molded from real boards
- Protective Film — removable film protects the face of the trim from scuffs and dirt
- Superior quality and excellent dimensional accuracy for tight, consistent joints
- Meets ICC and CCMC code requirements
- 25-year limited warranty
- Highly resistant to UV yellowing — no painting required for natural white finish
- FinishedEdge™ — heat-sealed edges prevent dirt from collecting on surface
- Smooth Finish on Reverse — creates the appearance of clean, freshly painted wood
- Cuts and mills with traditional woodworking tools
- Class A (Class 1) Flame Spread Classification
- NAHB Research Center Green Approved
- 12 SKUs across 7 classic profile shapes — cove, baseboards, and casings

## Profiles & Specifications

645000


PVC Cove (A-8) 16'



Length	16'
Height / Width	3/4"
Thickness	3/4"

645600


PVC Cove (A-8) 8'



Length	8'
Height / Width	3/4"
Thickness	3/4"

646100


PVC Cove (A-8) 12'



Length	12'
Height / Width	3/4"
Thickness	3/4"

645100


PVC Regular Baseboard (A-1) 8'



Length	8'
Height / Width	3-1/8"
Thickness	5/16"

645400

PVC Regular Casing (A-5) 7'



Length	7'
Height / Width	2"
Thickness	5/16"

645500


PVC Classic Casing (A-6) 84"



Length	84"
Height / Width	2-3/4"
Thickness	9/16"

645200


PVC Colonial Baseboard (A-2) 8'



Length	8'
Height / Width	3"
Thickness	7/16"

645900


PVC Colonial Baseboard (A-2) 12'



Length	12'
Height / Width	3"
Thickness	7/16"

646000


PVC Colonial Baseboard (A-2) 16'



Length	16'
Height / Width	3"
Thickness	7/16"

646200


PVC Century Baseboard (A-35) 8'



Length	8'
Height / Width	3-1/4"
Thickness	9/16"

646300


PVC Century Baseboard (A-35) 12'



Length	12'
Height / Width	3-1/4"
Thickness	9/16"

646400

PVC Century Casing (A-40) 7'



Length	7'
Height / Width	2-1/4"
Thickness	11/16"

## Certifications & Testing Standards

Restoration Millwork® Interior PVC Trim meets or exceeds the following Canadian and international performance standards.

- Flame Spread ASTM E84 — Class A (Class 1)
- Code Compliance — ICC and CCMC
- NAHB Research Center Green Approved

## Installation Guide

---

- 1 Installs with standard woodworking tools — saw, nail gun, miter box
- 2 Use PVC cement for all mitre and scarf joints to manage expansion/contraction
- 3 Recommended adhesives: Extreme PVC Trim Welder® or Partite® Adhesive
- 4 Nail or screw directly to studs or blocking — pre-drill near ends to prevent splitting
- 5 Leave 1/8" expansion gap at all butt joints; caulk with paintable latex after installation
- 6 Clean cuts with fine-tooth carbide blade; sand lightly for tight fits
- 7 Prime all cut ends and field-applied paint with 100% acrylic latex for best adhesion



## Ready to order?

Submit your spec list and we'll respond with pricing and availability - usually within one business day.

**WEB**

[promaterials.ca](http://promaterials.ca)

**PHONE**

(905) 836-7272

**EMAIL**

[info@promaterials.ca](mailto:info@promaterials.ca)

**ADDRESS**

Unit 5, 1235 Journey's End Cir, Newmarket, ON