

RESTORATION MILLWORK®
CERTAINTEED

Restoration Millwork® PVC Sheets

SKU: CT-RM-PVC-SHEETS

GAUGE

3/8" · 1/2" · 5/8" · 3/4" · 4/4"

WARRANTY

25-year limited warranty

PROFILES

Smooth · Wood Grain/Smooth —
thicknesses 3/8", 1/2", 5/8", 3/4", 4/4" —
4'x8', 4'x10', 4'x12'

Restoration Millwork® PVC Sheets by CertainTeed are large-format cellular PVC panels engineered for applications that demand smooth, flat, low-maintenance surfaces — soffits, pop-out bay windows, raised panels, dormers, and custom architectural details. Available in five thicknesses (3/8", 1/2", 5/8", 3/4", and 4/4") in 4'x8', 4'x10', and 4'x12' sheet sizes, with a Smooth finish on both sides or a reversible Wood Grain/Smooth option. All sheets ship natural white and accept paint for colour matching. FinishedEdge™ heat-sealed edges and TrueTexture™ woodgrain detailing are standard. Class A Flame Spread rated, ICC and CCMC compliant, NAHB Research Center Green Approved, and backed by a 25-year limited warranty.

Key Features

- Natural white and ready to install
- Can be painted to complement with exterior colors
- Class A (Class 1) Flame Spread Classification
- Low-maintenance, long-lasting material
- 25-year limited warranty
- TrueTexture™ — woodgrain finish molded from real boards
- Protective Film — removable film protects the face of the trim from scuffs and dirt
- Highly resistant to UV yellowing
- Cuts and mills with traditional woodworking tools
- Superior quality and excellent dimensional accuracy
- Meets ICC and CCMC code requirements
- FinishedEdge™ — edges are heat sealed to prevent dirt from collecting on surface
- Smooth Finish on Reverse — creates the appearance of clean, freshly painted wood

Profiles & Specifications

MSHSM544800

PVC Sheet Smooth 4/4"×4'×8'



Length	8 ft.
Height / Width	4 ft.
Thickness	4/4"

MSHSM1241000

PVC Sheet Smooth 1/2"×4'×10'



Length	10 ft.
Height / Width	4 ft.
Thickness	1/2"

MSHSM1241200


PVC Sheet Smooth 1/2"×4'×12'



Length	12 ft.
Height / Width	4 ft.
Thickness	1/2"

MSHSM3441200


PVC Sheet Smooth 3/4"×4'×12'



Length	12 ft.
Height / Width	4 ft.
Thickness	3/4"

MSHSM5841200


PVC Sheet Smooth 5/8"×4'×12'



Length	12 ft.
Height / Width	4 ft.
Thickness	5/8"

MSHSM5441200

PVC Sheet Smooth 4/4"×4'×12'



Length	12 ft.
Height / Width	4 ft.
Thickness	4/4"

MSHR384800

PVC Sheet Wood Grain/Smooth 3/8"×4'×8'



Length	8 ft.
Height / Width	4 ft.
Thickness	3/8"

MSHR124800

PVC Sheet Wood Grain/Smooth 1/2"×4'×8'



Length	8 ft.
Height / Width	4 ft.
Thickness	1/2"

MSHR344800

PVC Sheet Wood Grain/Smooth 3/4"×4'×8'



Length	8 ft.
Height / Width	4 ft.
Thickness	3/4"

Certifications & Testing Standards

Restoration Millwork® PVC Sheets meets or exceeds the following Canadian and international performance standards.

- Flame Spread ASTM E84 — Class A (Class 1)
- Code Compliance — ICC and CCMC
- NAHB Research Center Green Approved

Installation Guide

- 1 Use PVC cement for all mitre and scarf joints to control expansion and contraction
- 2 Recommended adhesives: Extreme PVC Trim Welder® or Partite® Adhesive
- 3 Score and snap for straight cuts; use a fine-tooth circular saw blade for custom shapes
- 4 Cuts and mills with standard woodworking tools — no special blades required
- 5 Remove protective film after installation to avoid adhesive residue
- 6 Refer to the Kaycan Restoration Millwork® installation manual for complete fastener schedules and gap allowances



Ready to order?

Submit your spec list and we'll respond with pricing and availability - usually within one business day.

WEB

promaterials.ca

PHONE

(905) 836-7272

EMAIL

info@promaterials.ca

ADDRESS

Unit 5, 1235 Journey's End Cir, Newmarket, ON